

Overview

Product information



RA-EBBF-2010-F-25040000001

Male float connector for exchange battery. Rated current: 60A; Rated voltage: 72V DC; Withstand voltage: 1500V AC; Insulation resistance > 500M Ω ; Mechanical life $\geq$ 5000 times; Pull out force > 50N; Operating temperature: -40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Product advantages

- ☒ The products are matched with each other and have the function of positive and negative insertion
- ☒ The floating amount when the product is inserted can compensate the gap between the vehicle body and the battery
- ☒ The guide post is aligned and inserted, which is convenient and fast

Product certification

RoHS

Technical data

Product drawing

3D model

□

Marking

Series	DA
	DEE
	DQ
	DF

technical parameter

insulation resistance	$\geq 500\text{M}\Omega$
Mechanical life	≥ 5000 次

versions

Connection method	Spring cage connection
Female/Male	Male
Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	20
	1
	24

Accessories

Business data

Order number	25040000001
Packing unit	
Minimum order quantity	
Products weight (without packaging)	