

Overview

Product information



SA-EBBM-2003-F-25060000002

Socket with direct plug in and out. Rated current: 20A; Rated voltage: 110V DC; Withstand voltage: 500V AC; Insulation resistance > 100M Ω ; Protection grade meet IP67 for socket only; Mechanical life $\geq$ 3000 times; Pull out force > 20N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Product advantages

- ☒ Fast direct plug connection
- ☒ After plugging in place, it has auditory and visual feedback
- ☒ High plug life
- ☒ Beautiful appearance, more in line with human functional design

Product certification

RoHS

Technical data

Product drawing

3D model

☐

Marking

classification	Insert
Series	DD
	DE
	DM

technical parameter

insulation resistance	$\geq 100\text{M}\Omega$
Mechanical life	≥ 3000 次

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	3A
	10A
	6B
	10B
	16B
	24B
	48B
Number of positions	4
	2

Environmental parameters

Degree of protection	MatchingIP67
----------------------	--------------

Accessories

Business data

Order number	25060000002
Packing unit	
Minimum order quantity	
Products weight (without packaging)	