

Overview

Product information



RM-EBBH-2006-M-1000-00A(H)-250800000001

Charging and discharging plug at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500MΩ; Protection grade: IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 20N; Working temperature: - 40 ~ 105 °C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

Product advantages

- ☑ Compact structure and high space utilization
- ☑ Adopt bayonet locking structure to prevent accidental unlocking
- ☑ Direct plug operation, convenient and fast
- ☑ Signal pin No.: 0~8 pins
- ☑ Multiple auditory and visual feedback are inserted in place
- ☑ Beautiful appearance, fit human functional design

Product certification

RoHS

Technical data

Product drawing

3D model

□

Marking

Series	DA
	DD
	DF

technical parameter

insulation resistance	≥500MΩ
Mechanical life	≥3000次

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	15
	25
	32
	42

Environmental parameters

Degree of protection	MatchingIP67
----------------------	--------------

Accessories

Business data

Order number	25080000001
Packing unit	
Minimum order quantity	
Products weight (without packaging)	

