

## Overview

### Product information



**DGB40-12010000463**

Transfer Type, Rated voltage(UL): 600V, pitch: 40mm, Color: black, Contact surface: Tin

### Product advantages

- ☒ Screw connection for worldwide use
- ☒ Screw connection for worldwide use
- ☒ Provide the cabinet and panel electrical transfer connections

### Product certification

## Technical data

### Product drawing

### 3D model

☐

### Wiring capacity

torque

40N.m

### Device properties

thread

M12

spacing

40mm

### Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (D)

600V

### Item properties

Type of installation

panel

Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Hexagonal screwdriver
Number of potentials	1
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059
--------------------	--------

#### Environmental data

Ambient temperature (operation)	-40°C~125°C(depending on derating curve)
---------------------------------	--

#### Accessories

#### Business data

Order number	12010000463
Packing unit	12
Minimum order quantity	/
Products weight (without packaging)	193.6