


Overview

Product information



DSIO1.5/3-11040000234

Sensor terminal blocks, connector method: Push-in connector, Rated voltage : 250 V, Rated current : 13.5 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

Product advantages

- ☑ Sensor terminal blocks.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With wire button, one word or cross screwdriver can release wire.
- ☑ Unique plug-in bridge, high circuit connection efficiency.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

Product certification



Technical data

Product drawing

3D model

□

IEC Electrical parameters

Rated current (III / 3)

13.5A

UL Electrical parameters

Rated voltage

300V

Rated current

15A

Wiring data

Conductor cross section flexible (ferrule without plastic sleeve)

0.14-1.5mm²

Conductor cross section flexible (ferrule with plastic sleeve)	0.14-0.5mm ²
2 flexible conductors with a TWIN ferrule	/
Strip length	8~10mm
Conductor cross section solid	0.14~1.5mm ²
Conductor cross section flexible	0.14~1.5 mm ²
Conductor cross section solid AWG	26~14

Environmental conditions

Ambient temperature (storage / transport)	-25℃~60℃
Ambient temperature (operation)	-40℃ ~ 105℃ (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	250V
Rated surge voltage	4KV

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Electrical performance test

Voltage drop	≤3.2mV
--------------	--------

Temperature rise test	≤45 K
-----------------------	-------

Dimension

NS 35/7,5 Height	41.5mm
End plate width	2.2mm
NS 35/15 Height	49mm
length	74.4mm
width	3.5mm
Height	34mm

Overview

Insulating material group	I
standard test	IEC60947-7-1
Connection type	In line connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessories

Marker

Top marker	ZSF3.5
Side marker	ZSF3.5
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.4x2.5
---	---------

Bridge	DFBXX-3.5
End cover	D-DSIO1.5/3-1

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11040000234
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	6.118