


Overview

Product information



DS16-TW-PE-11040000192

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.5 mm² - 25 mm², AWG: 20 - 4, Width: 12.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

Product advantages

- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

Product certification



Technical data

Product drawing

3D model

IEC Electrical parameters

Rated voltage (III / 3)

/

Rated current (III / 3)

/

UL Electrical parameters

Rated voltage

/

Rated current

/

Wiring data

Conductor cross section flexible (ferrule without plastic sleeve)

0.5-16mm²

Conductor cross section flexible (ferrule with plastic sleeve)	0.5-16mm ²
2 flexible conductors with a TWIN ferrule	1.5-4mm ²
Strip length	18mm
Conductor cross section solid	0.5~25mm ²
Conductor cross section flexible	0.5~16mm ²
Conductor cross section solid AWG	20~4

Environmental conditions

Ambient temperature (storage / transport)	-25℃~60℃
Ambient temperature (operation)	-40℃ ~ 105℃ (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Dimension

NS 35/7,5 Height	53.3mm
End plate width	2.2mm
NS 35/15 Height	60.8mm
length	100.4mm
width	12.2mm
Height	45.8mm

Overview

Insulating material group	I
standard test	IEC60947-7-2
Connection type	In line connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessories

Marker

Top marker	ZB10 / ZS12
Side marker	ZSF12
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	1x5.5
Bridge	/
End cover	D-DS16-TW

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11040000192
Packing unit	10
Minimum order quantity	10
Products weight (without packaging)	52.27