

#### Overview

#### Product information



# Relay module-DM108-RM-08-PN-2-4M-01A(H)-30030000045

ordinary Relay Module, with 20P Horn connector, with relay Socket ,8 ordinary relays can be installed, with 1C/O, with indicator light, Omron relay, PNP or NPN signal can be input (Please contact us for relay replacement)

#### Product advantages

- ☑ Each signal channel and power supply voltage have LED status indicators
- ☑ Pluggable ordinary relay, with 1C/O changeover contact, one-to-one output at the output terminal
- ☑ Freewheeling diode for each signal path
- ☑ Prefabricated cables, plug and play, fast wiring

Product certification

_		
Tec	hnica	l data

#### Product drawing

3D model

#### Overview

Installation location	Arbitrary
Number of channels	8
Shell Insulation Materials	PVC/PA66
color	green

## Dimension

width	125mm
Height	70mm
length	110.5mm

## Enter technical data

Rated input voltage	24VDC
Input voltage range relative to UN	0.91.1
protected name	Polarity protection
Protection circuits/components	Polarity Protection Diode
Status display/channel	green

# Export technical data

contact type	1C/O
Maximum switching voltage	240VAC 30VDC
Limit continuous current	16A
Fault monitoring (open circuit/short circuit)	no

## output connection data

connection name	output
Connection method	screw connection
Stripping length	6-7mm
thread	M3
connection volume	8
number of digits	3
Hard conductor cross section	1.0 2.5mm²
Flexible conductor cross section	1.0 2.5mm²
Connectable guide cross section AWG	2812AWG

## Enter connection data

connection name	enter
Connection method	IDC/MIL connector + screw connection
connection volume	1

number of digits	20
Environmental data	
Ambient temperature (operation)	-20 °C 70 °C
Ambient temperature (storage / transport)	-20 °C 70 °C
standards/Regulations	
Standards/Regulations	IEC61810
Pollution level	3

ccessories	
Accessories	

Business data	
Order number	30030000045
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	360