

## Overview

#### **Product information**



# D48B-SE-2g-M40-21010000417

48BHoods,double levers,side entry,M40 Thread hole

## Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$  Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

## Technical data

## Product drawing

3D model

## Marking

| classification | Upper Housing/base |
|----------------|--------------------|
| Series         | В                  |
| Туре           | Top housing        |
| Specification  | High structure     |

#### versions

| Dimension            | 48B         |
|----------------------|-------------|
| locking Category     | Single lock |
| Wiring method        | Side entry  |
| Thread specification | 1x M40      |

### Material characteristics

| RoHS                          | conform                  |
|-------------------------------|--------------------------|
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |

# Technical specification

| Limiting temperatures | -40°C~+125°C |
|-----------------------|--------------|
| IP class              | IP65         |

## Accessories

# Business data

| Order number                        | 21010000417 |
|-------------------------------------|-------------|
| Packing unit                        | 100         |
| Minimum order quantity              | 1           |
| Products weight (without packaging) | 740         |