

Overview

Product information



D24B-SE-2g-M25-21010000335

24BHoods,double levers,side entry,M25 Thread hole

Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$ Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

Marking

| classification | Upper Housing/base |
|----------------|--------------------|
| Series | В |
| Туре | Top housing |
| Specification | Low structure |

versions

| Dimension | 24B |
|----------------------|-------------|
| locking Category | Single lock |
| Wiring method | Side entry |
| Thread specification | 1x M25 |

Material characteristics

| RoHS | conform |
|-------------------------------|--------------------------|
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |

Technical specification

| Limiting temperatures | -40°C~+125°C |
|-----------------------|--------------|
| IP class | IP65 |

Accessories

Business data

| Order number | 21010000335 |
|-------------------------------------|-------------|
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 246 |