

Overview

Product information



D10B-SEH-4g-M25-21010000024

10BHoods,Four levers,high structure,side entry,M25 Thread hole

Product advantages

- ☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

□

Marking

| | |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series | B |
| Type | Top housing |
| Specification | High structure |

versions

| | |
|----------------------|-------------|
| Dimension | 10B |
| locking Category | Double lock |
| Wiring method | Side entry |
| Thread specification | 1x M25 |

Material characteristics

| | |
|-------------------------------|--------------------------|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |

Technical specification

| | |
|-----------------------|------------|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

Accessories

Business data

| | |
|-------------------------------------|-------------|
| Order number | 21010000024 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 160 |