


Overview

Product information

**DE-024-F-21020000037**

Heavy-duty insert, Number of contacts: 24+PE, Dimension: 24B, Rated voltage : 500V, Rated current: 16A, Female insert, Screw connector

Product advantages

- ✓ Screw connection technology, applicable to a wide range of wire specifications;
- ✓ No need special tools, easy to operate;
- ✓ Less materials, easy to manage;
- ✓ With grounding protection.

Product certification



Technical data

Product drawing

3D model



Marking

classification

Insert

Series

DE

versions

Connection method

Screw connection

Female/Male

Female

Dimension

24B

Number of positions

24

PE Contacts

Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	500V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7mm
Rated torque	0.5N.m
Conductor cross sections (mm²)	0.75-2.5mm²
Conductor cross sections(AWG)	18-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Accessories

Screwdriver

/

Business data

Order number	21020000037
Packing unit	100
Minimum order quantity	5
Products weight (without packaging)	125.5