

| Overview  |   |   |
|---|---|---|
| Product information   |   |   |
|   | AC charging cable wi<br>of electric vehicles (E | 2A-V1-5.0M-2202000098<br>th vehicle charging plug and free outlet for fast charging<br>EVs) with alternating current (AC) via a type 2 vehicle jack<br>charging stations (EVSE) |
| Product advantages  |   |   |
| ☑ All Degson's vehicle AC plugs and p<br>☑ The surface of power and signal co<br>☑ Certified to IATF 16949:2016 system<br>☑ Ergonomic handle with additional ru | ntacts are silver-plated<br>m                   |   |
| Product certification   |   |   |
| CE LUVRheinland   | СВ  |   |
|   |   |   |
| Technical data  |   |   |
| Product drawing   |   |   |
| 3D model  |   |   |
|   |   |   |
| •   |   |   |
| - Environmental conditions  |   |   |
|   |   | 5000m(Above sea level )   |
| Environmental conditions  |   | 5000m(Above sea level )<br>-30 °C ~ 50 °C   |
| Environmental conditions Maximum altitude   |   |   |
| Environmental conditions          Maximum altitude         Ambient temperature (operation)  |   | -30 °C ~ 50 °C  |
| Environmental conditions          Maximum altitude         Ambient temperature (operation)         IP class   |   | -30 °C ~ 50 °C  |
| Environmental conditions          Maximum altitude         Ambient temperature (operation)         IP class         Electrical characteristics                  |   | -30 °C ~ 50 °C<br>IP54 (protection cover)   |

| Rated current of high-power contacts | 32  |
|--------------------------------------|---|
| Power contact rated voltage          | 250   |
| Quantity of signal contacts          | 2   |
| Signal contact rated current         | 2   |
|                                      | 24  |
| Signal contact rated voltage         | 30  |
| Resistance coding                    | 220Ω  |
| Temperature measurement              | PT1000                                      |
| Mechanical properties                |   |
| Insertion force                      | < 100N                                      |
| Pull out force                       | < 100N                                      |
| Marking material                     |   |
| Shell color                          | black                                       |
| EV charger color                     | black                                       |
| Cover color                          | black                                       |
| Customization basis                  | Provided according to customer requirements |
| Handle material area                 | Plastic                                     |
| Protective cover material            | Soft plastic                                |
| Flammability rating                  | V0  |
| Contact surface material             | Ag  |
| Environmental Product Compliance     |   |
| China RoHS                           | conform                                     |
| Cable                                |   |
|                                      | 3*6mm²+1*0.75mm²                            |
| Cable composition                    | 3*10AWG+1*18AWG                             |
|                                      |   |

| Wiring standard          | EN50620   |
|--------------------------|---|
|                          | IEC62893.3  |
| Wiring level             | 5 class   |
| Certification            | CE  |
|                          | СВ  |
|                          | τυν   |
| Cable outer diameter     | 13±0.5mm  |
| Wire type                | Straight line   |
| Cable resistance         | ≤ 0.0033 $\Omega$ /m (Based on the power core, at an ambient temperature of 20°C) |
| Outer sheath,color       | black   |
| Minimum bend radius      | 78mm  |
| Outer sheath, material   | PUR   |
| Dimension                |   |
| Vehicle connector height | 79mm(Vehicle charging connector)  |
| Vehicle connector depth  | 222.3mm(Vehicle charging connector)   |
| Cable length             | 5000±50mm   |
| Strip length             | 100±10mm  |
| width                    | 70mm  |

## Accessories

## Business data

| Order number           | 2202000098 |
|------------------------|------------|
| Packing unit           | 5pcs/box   |
| Minimum order quantity | 5          |

| Products weight (without |  |
|--------------------------|--|
| packaging)               |  |