


## Overview

## Product information

**WS10-TW-11030000023**

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 57 A, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 24 - 8, Width: 10 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

## Product advantages

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Unique plug-in bridge, high circuit connection efficiency;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

## Product certification



## Technical data

## Product drawing

## 3D model

## Overview

|                                           |                        |
|-------------------------------------------|------------------------|
| Connection method                         | spring-cage connection |
| Number of rows                            | 1                      |
| number of connections                     | 3                      |
| Open-end side panels                      | Yes                    |
| Insulation Materials                      | PA                     |
| Flame retardant grade, in line with UL 94 | V0                     |
| Insulating material group                 | I                      |

|               |              |
|---------------|--------------|
| standard test | IEC60947-7-1 |
|---------------|--------------|

#### Dimension

|                  |        |
|------------------|--------|
| width            | 10mm   |
| End plate width  | 2.5mm  |
| Height           | 42mm   |
| NS 35/7,5 Height | 42.5mm |
| NS 35/15 Height  | 50mm   |

#### Wiring data

|                                   |                       |
|-----------------------------------|-----------------------|
| Strip length                      | 13~14mm               |
| Conductor cross section solid AWG | 24~8                  |
| Conductor cross section solid     | 0.2~10mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~10mm <sup>2</sup> |

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 57A  |
| Rated surge voltage     | 8KV  |

#### UL Electrical parameters

|               |      |
|---------------|------|
| Rated voltage | 600V |
| Rated current | 50A  |

#### Environmental conditions

|                                           |                                               |
|-------------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)           | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport)     | 25%~75%                                       |
| Ambient temperature (storage / transport) | -25°C~60°C                                    |

#### Mechanical performance test

|                     |                 |
|---------------------|-----------------|
| Mechanical strength | Passed the test |
|---------------------|-----------------|

|                             |                                 |
|-----------------------------|---------------------------------|
| Fixing support              | Passed the test                 |
| Rotational Pull Test        | Passed the test                 |
| Electrical performance test |                                 |
| Voltage drop                | ≤3.2mV                          |
| Temperature rise test       | ≤45 K                           |
| Safety test                 |                                 |
| Anti-finger touch           | Passed the test                 |
| Environmental protection    |                                 |
| RoHS                        | No excessive harmful substances |
| REACH SVHC                  | Lead 7439-92-1                  |

## Accessories

### Marker

|                |                        |
|----------------|------------------------|
| Top marker     | ZB10 / WB5             |
| Side marker    | DEK6                   |
| Marker support | DTH5-25×5 / DTH5-25×12 |
| Warning cover  | EEA10                  |

### Accessories

|                                                    |           |
|----------------------------------------------------|-----------|
| Slotted screwdriver size (Blade thickness x Width) | 0.8×5.5   |
| Adjacent jumper (2P)                               | WFA10     |
| Alternate jumper (2P)                              | WFB10     |
| Staggered jumper (2P)                              | /         |
| End cover                                          | D-WS10-TW |

### Installation

|           |                     |
|-----------|---------------------|
| End clamp | E-WS N / E-PC-1100A |
|-----------|---------------------|

|                               |                                       |
|-------------------------------|---------------------------------------|
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB10  |
| Marker cards  | DBE-1 |

#### Accessories

|           |                      |
|-----------|----------------------|
| End cover | D-WS10-TW            |
| Bridge    | WFA10                |
| End clamp | E-WS                 |
| DIN rail  | NS35/7.5-1000-00A(H) |

#### Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 11030000023 |
| Packing unit                        | 20          |
| Minimum order quantity              | 20          |
| Products weight (without packaging) | 30.635      |