

Overview

Product information



PMSH-M12D-04P-FF-SL8A01-20030001047

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,Straight,M12,Coding D,Shielded,Trimming cable end,Cable length:1m

Product advantages

☑ Sealing optimization, protection level up to IP68

☑Meet the harsh environment

☑Suitable for various occasions connection technology

 $\ensuremath{\square}$ Compatible with the international and domestic same series products

Product certification

ROHS REACH

_		
Tec	hnical	l data

Product drawing

3D model

Environmental conditions

Ambient temperature	-25℃85℃
IP class	IP68

General parameters

Rated current	4A
Rated Current	250V
Number of potentials	4
Insulation resistance	≥ 100 MΩ
Error-proof coding	D-Code

Overvoltage level	П
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

	Standards/specifications	IEC 61076-2-101
--	--------------------------	-----------------

Cable

Cable type	PVC Black
Cable type(abbreviation)	PVC
UL AWM form	UL2517
Cross section	0.34mm²
AWG signal wire	22AWG
Wire structure Signal wire	17/0.16mm²
Core diameter (including insulation layer)	1.30±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black knitting
Thickness, insulation	0.6mm
Cable outer diameter D	5.4 ±0.2mm

Outer sheath, material	PVC
Conductor insulation material	PVC
Conductor material	Tinned copper
Conductor resistance	Maximum 59.4Ω/km (at 20 °C))
Nominal cable voltage	300V
Cable test voltage	2000V
Flame retardant	Comply with UL 758/1581 FT1 standard
Halogen free	Yes
Dimension	
Cable length	1m

Accessories		
Accessories		
Sealing cap	CAP-M12-MP-8001	

Business data	
Order number	20030001047
Packing unit	I
Minimum order quantity	100
Products weight (without packaging)	/