

Overview

Product information



PM-M12A-05P-MM-SR8D01-20030000699

Sensor/Actuator Cable, PUR, black, UL20549, Male plug, acodado M12, Coding A,Unshielded,Trimming cable end,Cable Cable length:1m,UL Certification

Product advantages

☑ Sealing optimization, protection level up to IP68

☑Meet the harsh environment

☑Suitable for various occasions connection technology

 $\ensuremath{\square}$ Compatible with the international and domestic same series products

Product certification



cSAL BOHS REACH CSAL



Technical data

Prod	1	450		~~
P100	luct	ura	1 VVII	IU

3D model

Environmental conditions

Ambient temperature	-25℃80℃
IP class	IP68

General parameters

Data di sussissi	4A
Rated current	60V
Number of potentials	5
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101	

Cable

Cable type	PUR Black
Cable type(abbreviation)	PUR
UL AWM form	UL20549
Cross section	0.34mm²
AWG signal wire	22AWG
Wire structure Signal wire	17/0.16mm²
Core diameter (including insulation layer)	1.30±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black 5 Gray
Thickness, insulation	0.6mm
Cable outer diameter D	5.4 ±0.2mm

Outer sheath, material	PU
Conductor insulation material	PE
Conductor material	Tinned copper
Insulation resistance	≥100MΩ
Conductor resistance	Maximum 59.4Ω/km (at 20 °C))
Nominal cable voltage	300V
Cable test voltage	2000V
Flame retardant	Comply with UL 758/1581 FT2 standard
Oil resistance	No
Dimension	
Cable length	1m

Accessories Sealing cap CAP-M12-FP-8001	Accessories		
Sealing cap CAP-M12-FP-8001	Accessories		
	Sealing cap	CAP-M12-FP-8001	

Business data	
Order number	20030000699
Packing unit	
Minimum order quantity	100
Products weight (without packaging)	1