

| Overview   |                       |  |
|--|-----------------------|--|
| Product information  |                       |  |
|  | PCB spring terminal   | 0-DB-10060002582<br>blocks,Rated current:76A.Rated voltage<br>:10.0mm,Color:green,Contact surface :Tin |
| Product advantages   |                       |  |
| <ul> <li>PUSH-IN connection technology,</li> <li>Different poles can be combined</li> <li>Universal installation method, su</li> </ul> | through the side lock |  |
| Product certification  |                       |  |
|  | EAC                   |  |
| Technical data Product drawing 3D model  |                       |  |
|  |                       |  |
| Processing notes   |                       |  |
| Process  |                       | Wave soldering/manual soldering  |
| Connection capacity  |                       |  |
| Conductor cross section solid  |                       | 0.2~16mm²  |
| Conductor cross section flexible   |                       | 0.2~16mm²  |
| AWG  |                       | 20~4AWG  |
| Strip length   |                       | 17mm   |
| Electrical parameters UL   |                       |  |
| Rated voltage (B)  |                       | 600V   |
| Rated voltage (C)  |                       | 600V   |

| Rated voltage (D) | 600V |
|-------------------|------|
| Rated current (B) | 70A  |
| Rated current (D) | 5A   |
| Rated current (C) | 70A  |

## Electrical parameters IEC

| Rated voltage              | 1000V |
|----------------------------|-------|
| Rated voltage(III/3)       | 1000V |
| Rated current              | 76A   |
| Rated voltage(III/2)       | 1000V |
| Rated voltage(II/2)        | 1000V |
| Rated surge voltage(III/3) | 8KV   |
| Rated surge voltage(III/2) | 8KV   |
| Rated surge voltage(II/2)  | 8KV   |

## Item properties

| Connection direction | 0°                         |
|----------------------|----------------------------|
| Type of installation | PCB welding                |
| Pin arrangement      | Double-row of misalignment |
| Connection method    | Push-in spring connection  |
| Pitch                | 10mm                       |
| Number of potentials | 2                          |
| Pluggable or not     | no                         |
| Number of rows       | 1                          |
| Material data        |                            |
| Environmental items  | Compliant with REACH/RoHS  |

| Contact material                | copper                                    |
|---------------------------------|---|
| Contact point metal surface     | tin-plated                                |
| Contact zone metal surface      | tin-plated                                |
| Insulation Materials            | PA66                                      |
| Insulating material group       | Ι   |
| Flammability rating             | UL94V-0                                   |
| Mechanical tests                |   |
| Test Specification              | IEC60947/UL1059                           |
| Environmental data              |   |
| Ambient temperature (operation) | -40 ℃~105 ℃ (depending on derating curve) |

| Accessories         Coding strip       /         Bridge       /         Marking strip       /         Others       / |  |
|--|--|
| Bridge       /         Marking strip       /         Others       /  |  |
| Marking strip     /       Others     /   |  |
| Others /   |  |
|  |  |
|  |  |
| Tool   |  |
| Operating tool /   |  |
| Screwdriver /  |  |

| Business data          |             |
|------------------------|-------------|
| Order number           | 10060002582 |
| Packing unit           | 165         |
| Minimum order quantity | 30          |

| Products weight (without |  |
|--------------------------|--|
| packaging)               |  |